

Avoid Misreads & Violations

Mounting your transponder is critical to avoiding misreads and the potential for unwanted violations. Each truck has its nuances, if you have any questions or have experienced recurring issues going through toll plazas; make sure to call BESTPASS customer support before mounting your transponder @ 1-888-410-9696 Option 1 or email Support@Bestpass.com

Exterior Transponder Mounting

License plate mounts should be fastened using the screws that hold the plate. Arrows on the tabs should point up.

Roof Mounts should be placed on a flat portion near the front of the roof. Arrows on the tabs should point toward the front of the vehicle. Do not place near the GPS unit or any antenna as this may interfere with the EZ-Pass device signal.

Interior Transponder Mounting

Toll only windshield tags should be mounted at the top center of the windshield unless there is a metal visor. In this case they should be mounted at the bottom center. For those vehicles with windshield rear view mirrors the toll only transponder should be mounted behind and to the right of the mirror.

FUSION transponders (toll & weigh station bypass) should be mounted to the left of center and near the bottom of the windshield. The device must be visible from the driver seat in order to see the lights when approaching weigh stations.

Peterbilt windshields are configured so that the normal mounting of the FUSION transponder may not work well. This creates the problem of the transponder signal not being directed upward to the antenna about the vehicle. If the windshield is split you should mount the transponder left of center at the bottom. An extra layer of Velcro at the top will tip the transponder back a fraction which corrects the problem. Other remedies include mounting the transponder "upside-down" or even sideways. If a correct position cannot be found a license plate or roof mount toll only transponder may be necessary. You can contact BESTPASS customer support for additional Velcro strips.

Place the Blue EZPass transponder as per the Interior Mounting Instructions for Fusion or Tolls Only on page 1, then place white Horizon transponder as shown below.

FUSION Example

Tolls Only Example



